

SYSTEM CONFIGURATION		CONFIGURATION FOR DISPLAY TYPE	
OPTION	VALUE		
MODEL	VF	1	
ACCESS	FRONT		
MODULE	MODULE TYPE		FULL COLOR
	MODULE POWER TYPE		GEN 4 (24 VOLT BUS)
	MODULE SIZE		9X15
	PIXEL PITCH		34
PIXEL HEIGHT	45		
PIXEL WIDTH	180		
TYPE	FULL MATRIX		
DISPLAY INTERFACE	1		
WIRING LAYOUT	ROWS		

PERIPHERAL CONFIGURATION			
OPTION	VALUE	ADDRESS	LOCATION
LIGHT (LUX)	AMBIENT	DEFAULT	ON DISPLAY INTERFACE
LIGHT (LUX)	FRONT	DEFAULT	ON DISPLAY INTERFACE
LIGHT (LUX)	REAR	DEFAULT	ON DISPLAY INTERFACE
LIGHT (LUX)	LINE	DEFAULT	ON DISPLAY INTERFACE
TEMP	EXTERNAL	DEFAULT	ON DISPLAY INTERFACE
TEMP	INTERNAL	DEFAULT	ON DISPLAY INTERFACE
TEMP	MODULE	DEFAULT	ON DISPLAY INTERFACE
HUMIDITY	INTERNAL	DEFAULT	ON DISPLAY INTERFACE
ISOLATION BOARD	3	--	ON DISPLAY INTERFACE
DOOR SWITCH (SIGN)	1	--	--
RPM SENSORS	6	--	--
AIRFLOW SENSORS	6	--	--
CABINET HEATERS	NO	--	--
DEFOG HEATERS	YES	--	--
FACE FANS	NO	--	--
INTAKE FANS	YES	--	--
BEACONS	0	--	--
SURGE SUPPRESSORS	1	--	--

ADVANCED SETUP			
	N/A	N/A	N/A
	N/A	--	N/A
MINI DC I/O 1	--	--	ON DISPLAY INTERFACE
MINI DC I/O 2	--	--	ON DISPLAY INTERFACE
	--	--	N/A
	--	--	N/A
	--	--	N/A
	--	--	N/A

CUSTOM OPTIONS	
TRANSLATION TABLE	N/A
CONTROLLER CONFIGURATION PACKAGE	N/A
MULTI-DIRECTIONAL LIGHT SENSOR (MDLS)	N/A
I/O	N/A

Reference Drawings	
Schematic, VF-24X0, 120 VAC	DWG-1056399
Schematic, DC Power System, 2-4 Power Supplies, 34mm Signs	DWG-1067661
Shop Drawing, VF-24**-45x180-34-*	DWG-1159726
Site Interconnect, 1 AC Display with 1 Controller	DWG-3166540
Schematic, RPM and/or Airflow Sensors, Mini I/O, VCB	DWG-3177951
Schematic, Signal, VF-2420-45x180-34-RGB	DWG-4013528
Rear Electrical, VF-2420-45x180-34-RGB, ACP, AFS, Defog Heaters	DWG-4201715
Site Riser, 1 VF-2420-45x180-34-RGB, 1 TC, Vanguard® Field Controller in TC	DWG-4202111